


NEW 8 SERIES



10 NEW MODELS
FLOWS FROM 2-5 m³/min


150_{KG} LIGHTER THAN
 COMPARABLE
 MODELS

1 completely
 new 
screw element

 Compressor
 oil service
 once in
2 Years

 **11** years
 development
 of legendary
 HardHat[®] Canopy

 **under 60**
 minutes
 service time

 **12%**
 more
fuel efficient

15% 
 smaller
 footprint

100%
 guaranteed
 Buy-back value

 All models below **750KG** with full fuel tank, generator and aftercooler
ZERO extra driving licenses needed to tow ANY model

| Performance | | XAS 38 Kd | XAS 48 Kd | XAHS 38 Kd | XAS 58 Kd | XAS 68 Kd |
|--|---------------------|-----------|-----------|------------|-----------|-----------|
| Working pressure | bar (g) | 7 | 7 | 12 | 7 | 7 |
| | psi (g) | 100 | 100 | 175 | 100 | 100 |
| Free air delivery | CFM | 70 | 90 | 80 | 120 | 135 |
| | m ³ /min | 2,0 | 2,5 | 2,0 | 3,0 | 3,5 |
| Output power | kVA | - | - | - | - | - |
| Noise sound pressure level (Lp) | dB (A) | 70 | 70 | 70 | 70 | 70 |
| Noise sound power level (Lw) | dB (A) | 98 | 98 | 98 | 98 | 98 |
| Max. ambient temperature at sea level | °C | 50 | 50 | 50 | 50 | 50 |
| Min. starting temperature | °C | -10 | -10 | -10 | -10 | -10 |
| Min. starting temperature (cold start aid) | °C | -20 | -20 | -20 | -20 | -20 |

| Engine | | | | | | |
|-----------------------------------|-----|--------|--------|--------|--------|--------|
| Engine brand | | Kubota | Kubota | Kubota | Kubota | Kubota |
| Engine model | | D 722 | D 902 | V 1505 | V 1505 | V 1505 |
| Number of cylinders | | 3 | 3 | 4 | 4 | 4 |
| Power output @ normal shaft speed | kW | 14,9 | 18,5 | 26,5 | 26,5 | 26,5 |
| Full load RPM | rpm | 3400 | 3600 | 3000 | 3000 | 3000 |
| Unload RPM | rpm | 2000 | 2000 | 1850 | 1850 | 1850 |
| Engine oil capacity | l | 3,6 | 3,6 | 5,5 | 5,5 | 5,5 |
| Compressor oil capacity | l | 5,5 | 5,5 | 7,7 | 7,7 | 7,7 |
| Fuel tank capacity | l | 27 | 27 | 60 | 60 | 60 |

| Dimensions : box unit | | | | | | |
|-----------------------|----|------|------|------|------|------|
| Length | mm | 1570 | 1570 | 1940 | 1940 | 1940 |
| Width | mm | 1060 | 1060 | 1180 | 1180 | 1180 |
| Height | mm | 990 | 990 | 1150 | 1150 | 1150 |
| Weight box | kg | 440 | 440 | 650 | 650 | 650 |

| Transport dimensions : undercarriage | | | | | | |
|--------------------------------------|----|------|------|-------|-------|-------|
| Length | mm | 1960 | 1960 | 2290 | 2290 | 2290 |
| Width | mm | 1230 | 1230 | 1350 | 1350 | 1350 |
| Height | mm | 1250 | 1250 | 1400 | 1400 | 1400 |
| Weight portable | kg | 500 | 500 | < 750 | < 750 | < 750 |

OPTIONS

- Adjustable towbar with brakes
- Adjustable towbar without brakes
- Fixed towbar with brakes
- Fixed towbar without brakes
- DoT approved undercarriage
- Support mounted
- Support leg
- Jockey wheel
- Road signalization + wheel chocks
- Towing eye (DIN, NATO, AC, BNA, ITA ,GB , Ball coupling)
- Loose ball coupling
- Special colours
- Cold start
- Toolbox
- Aftercooler + water separator
- Aftercooler + water separator + reheater
- Aftercooler by-pass
- Additional fuel filter
- Safety cartridge
- Lubricator
- Non-return valve
- Tilt protection
- Air filter vacuum system
- Hose reel
- 4th O/L valve (simple attachment)
- DPF



8 STANDARD FEATURES

